





93~138 CFM

|  | Bearing | Rating Voltage (VDC) | Power Current (AMP) | Power Consumption (WATTS) | Speed (RPM) | Air Flow (CFM) | Static Pressure (Inch-H <sub>2</sub> O) | Noise (dBA) | Weight (g) | Curve |
|---|---------|----------------------|---------------------|---------------------------|-------------|----------------|---|-------------|------------|-------|
|   | ● VAPO  |                      |                     |                           |             |                |   |             |            |       |
| MEC0381V1-0000-A99  | ●       | 12                   | 0.845               | 10.1                      | 3100        | 138            | 0.36                                    | 48          | 218        | 1     |
| MEC0381V2-0000-A99  | ●       | 12                   | 0.5                 | 6.0                       | 2600        | 116            | 0.26                                    | 44          | 218        | 2     |
| MEC0381V3-0000-A99  | ●       | 12                   | 0.27                | 3.2                       | 2100        | 93             | 0.18                                    | 37          | 218        | 3     |
| MEC0382V1-0000-A99  | ●       | 24                   | 0.415               | 10.0                      | 3100        | 138            | 0.36                                    | 48          | 218        | 1     |
| MEC0382V2-0000-A99  | ●       | 24                   | 0.23                | 5.5                       | 2600        | 116            | 0.26                                    | 44          | 218        | 2     |
| MEC0382V3-0000-A99  | ●       | 24                   | 0.135               | 3.2                       | 2100        | 93             | 0.18                                    | 37          | 218        | 3     |
| MEC0384V1-0000-A99  | ●       | 48                   | 0.245               | 11.8                      | 3100        | 138            | 0.36                                    | 48          | 218        | 1     |
| MEC0384V2-0000-A99  | ●       | 48                   | 0.14                | 6.7                       | 2600        | 116            | 0.26                                    | 44          | 218        | 2     |
| MEC0384V3-0000-A99  | ●       | 48                   | 0.075               | 3.6                       | 2100        | 93             | 0.18                                    | 37          | 218        | 3     |

| Model              |  2BALL Sleeve | (VDC) | (AMP) | (WATTS) | (RPM) | (CFM) | (Inch-H <sub>2</sub> O) | (dBA) | (g) | Curve |
|--------------------|--|-------|-------|---------|-------|-------|-------------------------|-------|-----|-------|
| EEC0381B1-0000-A99 | ⊕  | 12    | 0.8   | 9.6     | 3100  | 138   | 0.36                    | 48    | 214 | 1     |
| EEC0381B2-0000-A99 | ⊕  | 12    | 0.48  | 5.8     | 2600  | 116   | 0.26                    | 44    | 214 | 2     |
| EEC0381B3-0000-A99 | ⊕  | 12    | 0.255 | 3.1     | 2100  | 93    | 0.18                    | 37    | 214 | 3     |
| EEC0382B1-0000-A99 | ⊕  | 24    | 0.4   | 9.6     | 3100  | 138   | 0.36                    | 48    | 214 | 1     |
| EEC0382B2-0000-A99 | ⊕  | 24    | 0.215 | 5.2     | 2600  | 116   | 0.26                    | 44    | 214 | 2     |
| EEC0382B3-0000-A99 | ⊕  | 24    | 0.13  | 3.1     | 2100  | 93    | 0.18                    | 37    | 214 | 3     |
| EEC0384B1-0000-A99 | ⊕  | 48    | 0.215 | 10.3    | 3100  | 138   | 0.36                    | 48    | 214 | 1     |
| EEC0384B2-0000-A99 | ⊕  | 48    | 0.125 | 6.0     | 2600  | 116   | 0.26                    | 44    | 214 | 2     |
| EEC0384B3-0000-A99 | ⊕  | 48    | 0.07  | 3.4     | 2100  | 93    | 0.18                    | 37    | 214 | 3     |

