



# AK175-C

172X50X51mm

**LIFE: 50000Hrs/40°C**

Low power consumption

Model No.	Rated VAC	Freq. Hz	Rated Input Current	Rated Input Watt	Rated Speed RPM	Max. Air Flow		Max. Static Pressure		Noise Level dB(A)
	V		A	W		M <sup>3</sup> /MIN	CFM	mm-H <sub>2</sub> O	inch-H <sub>2</sub> O	
AK1751HB-C	110 115	50/60	0.24/0.25	24/28	2600/3000	5.4/6.6	190/235	16/20	0.63/0.79	50±2
AK1751MB-C			0.17/0.21	20/23	2470/2370	4.7/4.8	165/170	13/14	0.51/0.55	40±2
AK1751LB-C			0.16/0.20	16/18	1600/1800	3.1/3.0	110/106	10/8	0.40/0.31	32±2
AK1752HB-C	200	50/60	0.12/0.16	24/28	2600/3000	5.4/6.6	190/235	16/20	0.63/0.79	50±2
AK1752MB-C	220		0.10/0.12	20/23	2300/2400	4.7/4.8	165/170	13/14	0.51/0.55	40±2
AK1752LB-C	240		0.09/0.16	16/18	1600/1800	3.1/3.0	110/106	10/8	0.40/0.31	32±2



<http://www.adda.com.tw>

10