


# UltraFlo™



## U60T Series

- ✓ Durable, Magnetically Stabilized NBRX Sleeve Bearing Design
- ✓ Current-Limit Protection
- ✓ Optional Open-Collector Tachometer or Locked Rotor Alarm
- ✓ Plastic Housing and Impeller Rated V-0
- ✓ 12V and 24V Models



## 60 x 25mm Tube Axial Cooling Fans

Model	Air Flow (CFM)	Max. Static Pressure (inwg)	Operating Voltage		Operating Current (A)	Input Power (W)	Fan Speed (rpm)	Sound Pressure (dBA)	Operating Temp.		L10 Life† (hours)
			Nominal (V)	Range (V)					Min. (°C)	Max. (°C)	
U60T12MUA7-51	23	0.24	12	7.0-13.8	0.16	1.9	4600	32.5	-10	+70	50,000
U60T24MUA7-51	23	0.24	24	20.4-27.6	0.07	1.7	4600	32.5	-10	+70	50,000
U60T12MGA7-51	19	0.18	12	7.0-13.8	0.11	1.3	3900	29.5	-10	+70	—
U60T24MGA7-51	19	0.18	24	20.4-27.6	0.06	1.4	3900	29.5	-10	+70	—
U60T12MHA7-51	15	0.12	12	7.0-13.8	0.10	1.1	3200	22.5	-10	+70	—
U60T24MHA7-51	15	0.12	24	20.4-27.6	0.05	1.2	3200	22.5	-10	+70	—
U60T12MMA7-51	11	0.07	12	7.0-13.8	0.06	0.7	2400	13.0	-10	+70	—
U60T24MMA7-51	11	0.07	24	20.4-27.6	0.03	0.7	2400	13.0	-10	+70	—









Air flow, current, speed and sound pressure ratings are at nominal operating voltage and zero static pressure. Current and power ratings are average expected values under those conditions. † L10 bearing life expectancy at T<sub>A</sub> = +40°C.™ UltraFlo is a brand trademark of Nidec Corporation. N/AJAB

### Recommended Standard Connectors


Connector Pitch	Manufacturer	Housing*	Contacts
1.50 mm	J.S.T.	ZHR- <i>n</i>	SHZ-002T-P0.5
2.00 mm	J.S.T.	PHR- <i>n</i>	SPH-002T-P0.5S
	Tyco/AMP	173977- <i>n</i>	Includes Contacts
2.50 mm	J.S.T.	EHR- <i>n</i>	SEH-001T-P0.6
	J.S.T. Tyco/AMP	XHP- <i>n</i> 171822- <i>n</i>	SXH-001T-P0.6 Includes Contacts
2.54 mm	Molex	2695	5159

\* The character "n" shown at the end of housing model names represents the number of contact positions available with that housing. ZHR-2, for example, identifies a housing with two contact positions.

# UltraFlo




## OPEN-COLLECTOR TACHOMETER




Option '-52'

## TYPICAL VALUES OF $V_{LOW}$ AS A FUNCTION OF $I_C$



## OPEN-COLLECTOR LOCKED ROTOR ALARM



Option '-53'